

GOLDSCOPE SD
GOLDSCOPE SD Pro
GOLDSCOPE SDD
GOLDSCOPE SDD Pro

X-Ray Fluorescence Measuring Instruments
 Optimized for Fast, Cost-effective and Non-destructive
 Analysis of Jewelry, Coins and Precious Metals



GOLDSCOPE SD



GOLDSCOPE SD Pro
 GOLDSCOPE SDD
 GOLDSCOPE SDD Pro

Description

The X-ray fluorescence measuring instruments of the GOLDSCOPE series are optimized for fast, cost-effective and non-destructive analysis of jewelry, coins and precious metals. Furthermore, the instruments are well suited for determining the thickness of gold coatings on sterling silver and rhodium coatings on gold alloys.

The GOLDSCOPE series comprises four different instruments to fulfill the specific demands from the fast purchase and sale of gold up to the high-precision analysis of precious metals.

Typical fields of application are the analysis of:

- Jewelry, precious metals and dental alloys
- Yellow and white gold
- Platinum and silver
- Rhodium
- Alloys and coatings

Outstanding accuracy and long-term stability are characteristics of all X-RAY systems from FISCHER. The necessity of recalibration is considerably reduced, saving time and effort.

The GOLDSCOPE SD instruments are equipped with a modern silicon PIN detector, which achieves high accuracy and good detection sensitivity. For even higher resolution, the GOLDSCOPE SDD instruments with their Silicon Drift Detectors (SDD) are available.

The fundamental parameter method by FISCHER allows for the analysis without calibration.

Design

The GOLDSCOPE instruments are designed as user-friendly bench-top instruments. Due to their compact design, the instruments are lightweight and require only little space.

For smallest footprint, the measurement chamber door of the GOLDSCOPE SD does not open upwards, but towards the front. Thus, you can place a notebook for operation onto the instrument, which saves even more space.

For quick and easy sample positioning, the X-ray source and detector assembly is located in the instrument's lower chamber. The measuring direction is from underneath the sample, which is supported by a transparent window.

The integrated video-microscope with zoom and crosshairs simplifies sample placement and allows for a precise measuring spot adjustment.

The entire operation and evaluation of measurements as well as the clear presentation of measurement data is performed on a PC, using the powerful and user-friendly WinFTM[®] software.

All GOLDSCOPE instruments fulfill DIN ISO 3497 and ASTM B 568.

Application

Recommended area of application

GOLDSCOPE SD	GOLDSCOPE SD Pro	GOLDSCOPE SDD	GOLDSCOPE SDD Pro
Small retail shops	High end retail showrooms, small assaying offices	Refineries, assaying offices and hall-marking centers	Hallmarking centers, jewelry manufacturing, assaying offices

General Specification

Intended use	Energy dispersive X-ray measuring instrument (EDXRF) to analyze precious metals
Design	GOLDSCOPE SD: Bench top unit with towards the front opening hood, GOLDSCOPE SD Pro, SDD, SDD Pro: Bench top unit with upwards opening hood
Measuring direction	Bottom up

Electrical Data

Power supply and consumption	AC 115 or 230 V, 50/60 Hz, max. 120 W without evaluation PC
Protection class	IP40

Environmental Conditions

Operating temperature	10 °C – 45 °C / 50 °F – 113 °F
Storage/Transport temperature	0 °C – 50 °C / 32 °F – 122 °F
Relative humidity	≤ 95 %

Sample Alignment

Sample positioning	Manually
Video microscope	High-resolution CCD colour camera for optical monitoring of the measurement location along the primary beam axis, Crosshairs with a calibrated scale (ruler) and spot-indicator, Adjustable LED illumination
Zoom factor	Digital 1x, 2x, 3x, 4x

Evaluation Unit

Computer	Windows®-PC
Software	WinFTM® optimized for GOLDSCOPE, including Gold Setup GOLDSCOPE with measuring applications for gold and jewelry

Standards

	GOLDSCOPE SD	GOLDSCOPE SD Pro	GOLDSCOPE SDD	GOLDSCOPE SDD Pro
CE approval	EN 61010, EN 61326			
X-Ray standards	DIN ISO 3497 and ASTM B 568			
Approval	Individual acceptance inspection as a fully protected instrument according to the German regulations „Deutsche Röntgenverordnung-RöV“.	Fully protected instrument with type approval according to the German regulations „Deutsche Röntgenverordnung-RöV“.		

Sample Stage

Design	Fixed sample support		
Max. sample weight [kg/lb]	13/29		
Usable sample placement area [mm/in]	305 x 490/ 12 x 19.3	310 x 320/ 12.2 x 12.6	
Max. sample height [mm/in]	130/5.1	90/3.5	

Dimensions	GOLDSCOPE SD	GOLDSCOPE SD Pro	GOLDSCOPE SDD	GOLDSCOPE SDD Pro
External dimensions Width x depth x height [mm/in] Weight [kg/lb]	405 x 588 x 426/ 16 x 23 x 17 approx. 45/99	403 x 588 x 365/16 x 23.2 x 14.4 approx. 45/99		
X-Ray Source				
X-ray tube	Tungsten tube, thermally stabilized		Micro-focus tungsten tube with beryllium window	
High voltage, three steps [kV] Primary filter, Material and thickness [µm/mils]	30, 40, 50 none	30, 40, 50 none	30, 40, 50 fixed Al 500/19.7	10, 30, 50 6x changeable: Ni 10/0.4 no filter Al 1000/39.4 Al 500/19.7 Al 100/3.9 Mylar® 100/3.9
Aperture (Collimator) Ø [mm/mils]	Fixed Standard 1,0/39 Option 0.6/24;	Fixed Standard 1,0/39 Option 0.6/24; 1.0/39 or 2.0/79	Fixed, Standard 1.0/39 Option 0.6/24; 1.0/39 or 2.0/79	4x changeable: 0.2/8; 0.6/24; 1.0/39; 2.0/79
Smallest measurement spot* Ø [mm/mils]	approx. 0.7/28*	approx. 0.7/28*	approx. 0.7/28*	approx. 0.3 /12*
	* depends on the measuring distance and on the aperture, the actual measurement spot size is shown in the video image			
X-Ray Detection				
Detector type	Silicon PIN detector peltier-cooled		Silicon Drift Detector (SDD), peltier-cooled	
Resolution fwhm for Mn-K _α [eV]	≤ 180		≤ 160	
Element range	S (16) to U (92)			Al (13) to U (92)
Measuring distance [mm/in]	0 – 25/0 – 1, Distance compensation with patented DCM method for simplified measurements at varying distances. For particular applications or for higher demands on accuracy an additional calibration might be necessary.			
Repeatability for gold, measurement time 60 sec	≤ 2 ‰	≤ 1 ‰ with aperture 1,0 mm	≤ 0,5 ‰ with aperture 1,0 mm	≤ 0,5 ‰ with aperture 1,0 mm
Order				
Order number	605-684	605-685	605-686	605-687
	Incl. Gold Setup GOLDSCOPE with factory-calibrated measuring applications for gold and jewelry			

Special GOLDSCOPE product modification and technical consultation on request

WinFTM® is a registered trademark of Helmut Fischer GmbH Institut für Elektronik und Messtechnik, Sindelfingen - Germany.
Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.

www.helmut-fischer.com

fischer®